

ग्रामोद्योग संचालनालय हाथकरघा
चतुर्थ तल, ब्लॉक-ए, इन्द्रावती भवन, अटल नगर नवा रायपुर 492002 (छ.ग.)
फोन नं.-0771-2511766 Email- handloomraipur@gmail.com


-:: नवीन करघे एवं अन्य सहायक उपकरणों क्रय हेतु निविदा आवेदन पत्र ::-

1. निविदा फार्म प्राप्त करने की अंतिम तिथि **28.10.2025** समय सायं 5:00 बजे तक
2. निविदा फार्म जमा करने का अंतिम तिथि **29.10.2025** समय दोपहर 12:00 बजे तक
3. निविदा फार्म खोलने की तिथि **29.10.2025** समय दोपहर 01:00 बजे
4. निविदा फार्म खोलने का स्थान सभा कक्ष, ग्रामोद्योग संचालनालय हाथकरघा प्रभाग, चतुर्थ तल, ब्लॉक-ए, इन्द्रावती भवन, नवा रायपुर अटल नगर।
5. निविदा फार्म प्राप्त करते समय निविदा प्रपत्र की राशि रु. **2,000/-** (अक्षरी राशि रु. दो हजार) मात्र कार्यालय में नगद जमा करना अनिवार्य होगा।
6. यदि निविदा फार्म वेबसाइट से डाउनलोड किया गया हो, तो उक्त निविदा फार्म जमा करते समय निविदा प्रपत्र की राशि रु. **2,000/-** (अक्षरी राशि रु. दो हजार) मात्र कार्यालय में नगद जमा करना अनिवार्य होगा।

संयुक्त संचालक
सक्षम अधिकारी


(अ) प्रारंभिक जानकारी		
1.	निविदाकर्ता फर्म/संस्थान का पूरा नाम	
2.	निविदाकर्ता फर्म/संस्थान का पूर्ण पता	
3.	मोबाईल नम्बर	
4.	ई-मेल	
5.	फर्म/कम्पनी/संस्थान के प्रोपाईटर/पार्टनर का नाम	

क्रमश:-2



6.	फर्म/कम्पनी/संस्थान के प्रोपाईटर/पार्टनर का पूर्ण पता	
7.	मोबाईल नम्बर	
8.	ई-मेल	
9.	निविदाकर्ता का व्यापारिक संस्था कहाँ स्थित है ?	
10.	फर्म/संस्थान का पंजीयन क्रमांक व दिनांक	
11.	फर्म/संस्थान का छत्तीसगढ़ राज्य में पंजीकृत जी.एस.टी. क्रमांक व दिनांक	
12.	फर्म/ प्रोपाईटर/पार्टनर का पेन (PAN) नम्बर	
13.	फर्म/कम्पनी/संस्थान के प्रोपाईटर/पार्टनर का आधार नम्बर	
14.	फर्म/संस्थान का वन विभाग का जीवित पंजीयन क्रमांक एवं दिनांक (करघे प्रदाय हेतु)	
15.	फर्म/संस्थान का उद्योग विभाग का जीवित पंजीयन क्रमांक एवं दिनांक (करघे प्रदाय हेतु)	
16.	करघे एवं अन्य सहायक उपकरण अन्य फर्म/ संस्थान को प्रदाय करने संबंधी विगत वर्षों का अनुभव विवरण (संग्रह करें)	

क्रमश:-3



//3//

प्रमाणित किया जाता है, कि नवीन करघे एवं अन्य सहायक उपकरणों के क्रय के लिए दर निर्धारण हेतु निविदा प्रपत्र में दी गई समस्त जानकारी सत्य एवं सही हैं। किसी प्रकार की त्रुटि/गलत जानकारी पाये जाने पर मैं स्वयं जिम्मेदार रहूंगा/रहूंगी।

स्थान-

हस्ताक्षर-

दिनांक-

नाम -

हैसियत-

सील -

संलग्न दस्तावेज -

01. फर्म/संस्थान का पंजीयन प्रमाण पत्र की छायाप्रति।
02. छत्तीसगढ़ राज्य में पंजीकृत जी.एस.टी. प्रमाण पत्र की छायाप्रति।
03. फर्म/प्रोपराईटर का पेन (PAN) नम्बर की छायाप्रति।
04. फर्म/प्रोपराईटर का विगत 03 वर्षों का (ITR) (यदि हो तो)
05. फर्म का वन विभाग का जीवित पंजीयन की छायाप्रति।
06. फर्म का उद्योग विभाग में जीवित पंजीयन की छायाप्रति।
07. नवीन करघे एवं अन्य सहायक उपकरणों अन्य फर्म/ संस्थान को प्रदाय करने संबंधी विगत वर्षों का अनुभव विवरण।

टीप:-

1. जो लागू हो उन्हें चिन्हांकित करें।
2. उपरोक्त के अतिरिक्त अन्य प्रमाण पत्र हों तो संलग्न करें।



संस्थान के प्रोपराईटर के हस्ताक्षर
एवं सील

ग्रामोद्योग संचालनालय हाथकरघा
चतुर्थ तल, ब्लॉक-ए, इन्द्रावती भवन, अटल नगर नवा रायपुर 492002 (छ.ग.)
फोन नं.-0771-2511766 Email- handloomraipur@gmail.com

-:: नवीन करघे एवं अन्य सहायक उपकरण सामग्रियों की निविदा हेतु नियम एवं शर्तें ::-

1. ग्रामोद्योग संचालनालय हाथकरघा प्रभाग नवा रायपुर अटल नगर छत्तीसगढ़ द्वारा निर्धारित एवं जारी निविदा प्रपत्र में ही निविदा मान्य की जावेगी ।
2. निविदा प्रपत्र निविदा प्रकाशन तिथि 04.10.2025 से दिनांक **28.10.2025** को सायं 5:00 बजे तक निविदा प्रपत्र शुल्क **2,000/-** (अक्षरी राशि रु. दो हजार) मात्र कार्यालय में नगद जमा कर प्राप्त कर सकते हैं अथवा ग्रामोद्योग संचालनालय हाथकरघा इन्द्रावती भवन नवा रायपुर के वेबसाइट **www.ruralindustries.cg.gov.in.** से डाउनलोड किया जा सकता है, किन्तु निविदा प्रपत्र जमा करने के पूर्व निविदा प्रपत्र शुल्क राशि रु. **2,000/-** (अक्षरी राशि रु. दो हजार) कार्यालय में नगद जमा करना होगा। निविदा प्रपत्र सील बंद लिफाफे में दिनांक **29.10.2025** को दोपहर 12:00 बजे तक जमा की जा सकेगी तथा प्राप्त निविदाएं दिनांक **29.10.2025** को दोपहर 1:00 बजे खोली जावेगी, चाहे तो निविदादाता अथवा उनके प्रतिनिधि निविदा खोलते समय उपस्थित रह सकते हैं।
3. निविदा प्रपत्र सावधानीपूर्वक भरी जावें, ओवर राइटिंग एवं कांट-छांट न हों ।
4. निविदा में समस्त कर जी.एस.टी., एफ.ओ.आर. एवं संस्था/बुनकरों के घर में परिवहन, स्थापित/फिटिंग सहित दर भरा जावे, उक्त दर के अतिरिक्त पृथक से कोई अन्य कर देय नहीं होगा।
5. आमंत्रित निविदा संचालक, ग्रामोद्योग संचालनालय हाथकरघा प्रभाग, इन्द्रावती भवन, चतुर्थ तल ब्लॉक ए, नवा रायपुर अटल नगर में नीचे उल्लेखित अनुसार सीलबंद “तीन लिफाफा” निर्धारित समयावधि में जमा करना होगा :-

(अ) प्रथम लिफाफा में - “संचालक, ग्रामोद्योग संचालनालय हाथकरघा” के नाम से बैंक डिमाण्ड ड्राफ्ट (भारतीय स्टेट बैंक अथवा अनुसूचित बैंक)

(टीप:- 1. प्रथम लिफाफे के ऊपर “बैंक डिमाण्ड ड्राफ्ट” अंकित करें।

क्रमश:-2



(ब) द्वितीय लिफाफा:-

01. फर्म/संस्थान का पंजीयन प्रमाण पत्र की छायाप्रति।
02. छत्तीसगढ़ राज्य में पंजीकृत जी.एस.टी. प्रमाण पत्र की छायाप्रति।
03. फर्म/प्रोपराईटर का पेन (PAN) नम्बर की छायाप्रति।
04. फर्म/प्रोपराईटर का विगत 03 वर्षों का (ITR) (यदि हो तो)
05. फर्म का वन विभाग का जीवित पंजीयन की छायाप्रति।
06. फर्म का उद्योग विभाग में जीवित पंजीयन की छायाप्रति।
07. नवीन करघे एवं अन्य सहायक उपकरणों अन्य फर्म/ संस्थान को प्रदाय करने संबंधी विगत वर्षों का अनुभव विवरण।

(टीप:- द्वितीय लिफाफे पर आवेदन के संलग्न दस्तावेज स्पष्ट अंकित करें।)


(स) तृतीय लिफाफा :-

तृतीय लिफाफे में संलग्न “परिशिष्ट-4” में नवीन करघे एवं संलग्न “परिशिष्ट-5” में अन्य सहायक उपकरण क्रय हेतु दर पत्रक रखा जावे।

(टीप- लिफाफे के ऊपर तृतीय लिफाफा नवीन करघे एवं अन्य सहायक उपकरण दर पत्रक अंकित करे।)

6. प्रथम लिफाफा शर्त अनुसार होने पर द्वितीय लिफाफा खोला जावेगा तथा द्वितीय लिफाफा शर्तानुसार पूर्ण पाये जाने पर तृतीय लिफाफा खोला जावेगा।
7. सफल निविदाकर्ताओं को क्रय आदेश के विरुद्ध अग्रिम देय नहीं होगा। सामाग्री प्रदाय करने के उपरान्त भौतिक एवं तकनीकी मापदण्डों अनुसार सत्यापन कमेटी के सत्यापन पश्चात ही भुगतान की जायेगी।
8. ग्रामोद्योग संचालनालय हाथकरघा द्वारा आवश्यकता अनुसार स्वीकृत निविदा दर पर क्रय आदेश देय होगा। स्वीकृत दर पर नवीन करघे एवं अन्य सहायक उपकरण निर्धारित समयावधि में एवं क्रय आदेश के अनुसार निर्धारित स्थान पर प्रदायकर्ता फर्म को नवीन करघे एवं अन्य सहायक उपकरण संबंधित संस्था के मुख्यालय अथवा बुनकरों के घरों पर पहुँचा कर देना होगा एवं स्थापित (फिटिंग) करके देने होंगे, जिसका परिवहन, स्थापित (फिटिंग) एवं अन्य व्यय पृथक से देय नहीं होगी।

क्रमश:-3



9. निविदाकर्ता का व्यापारिक संस्थान कहाँ स्थित है, जहाँ से वह भिन्न स्थानों पर सामग्री का प्रदाय करेगा, इसका पृथक से उल्लेख करना आवश्यक है।
10. नवीन करघे एवं अन्य सहायक उपकरणों की दरे स्वीकृति दिनांक से 01 वर्ष के लिये लागू होगी। संचालक की अनुमति से इसमें अधिकतम 03 माह के लिए वृद्धि की जा सकेगी।
11. प्रत्येक निविदा फार्म के साथ संबंधित वास्तविक निविदादाताओं को अलग-अलग सामाग्रियों के लिये अनुमानित क्रय मूल्य का 01 प्रतिशत अमानत राशि का भारतीय स्टेट बैंक अथवा अनुसूचित बैंक का डिमांड ड्राफ्ट प्रथम लिफाफा में जमा करना अनिवार्य होगा। अनुमानित क्रय मूल्य की राशि निविदा फार्म के साथ संलग्न “परिशिष्ट-3” “अनुमानित क्रय की मात्रा” के आधार पर होगी।
12. छत्तीसगढ़ शासन भण्डार क्रय नियम 2002 (विभागीय अधिसूचना दिनांक 05.03.2025 पर्यन्त अद्यतन) प्रावधानों के अनुसार अमानत राशि जमा करने हेतु लागू छूट दी जाएगी।
13. नवीन करघे एवं अन्य सहायक उपकरण सामग्री निर्धारित मापदण्ड एवं गुणवत्ता में सूखी लकड़ी के ही नवीन करघे तथा अन्य सहायक उपकरण प्रदाय करने होंगे अन्यथा सामग्री वापस की जावेगी। जिस पर होने वाले परिवहन सहित समस्त व्यय की जिम्मेदारी प्रदायकर्ता फर्म की होगी।
14. नवीन करघे एवं अन्य सहायक उपकरण क्रय की अनुमानित मात्रा समितियों के मांग/उपलब्ध बजट के अनुसार कम अथवा अधिक हो सकता है।
15. नवीन करघे हेतु तकनीकी मापदण्ड “परिशिष्ट-1” एवं अन्य सहायक उपकरण हेतु तकनीकी मापदण्ड “परिशिष्ट दो” संलग्न है।
16. प्रदायकर्ता फर्म को आदेश जारी होने के अधिकतम 45 दिवस के भीतर सामग्री प्रदाय करना अनिवार्य होगी।
17. स्वीकृत निविदा दर पर यदि एल-01 निविदाकर्ता के द्वारा सामग्री निर्धारित मापदण्ड एवं समय पर प्रदाय नहीं करने की स्थिति में द्वितीय निविदाकर्ता को एल-01 के स्वीकृत दर पर कार्य आदेश दिया जा सकेगा। इस हेतु एल-01 निविदाकर्ता की कोई भी आपत्ति स्वीकार नहीं की जावेगी।

क्रमश:-4



18. बिना कारण बताये निविदा निरस्त करना या निविदा तिथि में वृद्धि का अधिकार अधोहस्ताक्षरकर्ता के पास सुरक्षित रहेगा ।
19. किसी प्रकार के विवाद की स्थिति में संचालक ग्रामोद्योग संचालनालय हाथकरघा प्रभाग नवा रायपुर का निर्णय अंतिम एवं बंधनकारी होगा ।
20. किसी प्रकार की न्यायालयीन स्थिति निर्मित होने पर छत्तीसगढ़ राज्य के न्यायालय के अधीन होगा ।
21. निविदा में पात्र सफल निविदाकर्ता को क्रय आदेश जारी करने के पूर्व वास्तविक क्रय मूल्य का कम से कम 3 (तीन) प्रतिशत सुरक्षा निधि जमा करना होगा ।
22. निविदाकर्ता का पंजीयन छत्तीसगढ़ राज्य के जीएसटी विभाग में होना अनिवार्य है ।
23. निविदाकर्ता को किसी राज्य/संस्थान/विभाग द्वारा काली सूची में दर्ज नहीं किया गया है, उसका नॉन ज्यूडिशियल स्टॉम्प में प्रमाण पत्र संलग्न करना आवश्यक है ।
24. अनुमोदित निविदाकर्ता द्वारा क्रय आदेशानुसार समय पर सामग्री आपूर्ति न करने की दशा में अथवा अनावश्यक प्रभाव डालने की दशा में फर्म को काली सूची में दर्ज करने की कार्यवाही की जा सकेगी ।
25. संलग्न “परिशिष्ट-2” अनुसार अन्य सहायक उपकरणों जैसे :- Reed (Steel), Heald (Nylon) , Heald (Wire), Simple Wooden Shuttle (Weight not more than 230 gm.) , Half Compress Shuttle, Full Compress Shuttle , Nylon bobbin, Nylon Pirn का नमूना निविदा प्रपत्र के साथ संलग्न करे अथवा निविदा फार्म प्रस्तुत करने के समय उक्त सामग्रियों का नमूना प्रस्तुत करना अनिवार्य है, बिना नमूना के तृतीय लिफाफा नवीन करघे एवं अन्य सहायक उपकरण क्रय दर पत्रक नहीं खोला जावेगा ।



(श्याम धावड़े) IAS

संचालक
ग्रामोद्योग हाथकरघा
छत्तीसगढ़ रायपुर

परिशिष्ट-एक

नवीन करघे हेतु तकनीकी मापदण्ड पृथक से संलग्न है।

परिशिष्ट-दो

अन्य सहायक उपकरण क्रय हेतु तकनीकी मापदण्ड पृथक से संलग्न है।

परिशिष्ट-तीन

-:: नवीन करघे एवं अन्य सहायक उपकरण क्रय की अनुमानित मात्रा ::-

क्र.	विवरण	अनुमानित मात्रा
1	2	3
नवीन करघे :-		
1	फ्रेमलूम लोहा (56 इंच तक)	50
2	फ्रेमलूम (60 इंच तक)	127
3	फ्रेमलूम (60 इंच से अधिक)	12
योग :-		189
अन्य सहायक उपकरण :-		
1	टेक-अप एवं लेट-अप मोशन	102
2	न्यूमेटिक जेकार्ड	2
3	मोटोराइज्ड जेकार्ड	2
4	मल्टीपल बाक्स मोशन	2
5	मल्टीपल बूटी विविंग स्ले	2
6	ट्विन क्लाथ विविंग मेकेनिज्म	2
7	जेकार्ड	5
8	डॉबी	22
9	रीड	1160
10	हील्ड	1160
11	शटल	1440
12	बाबीन	20000
10	वार्प एवं फैब्रिक बीम	202
11	मोटोराइज्ड वार्पिंग मशीन	7
12	मोटोराइज्ड पिर्न/कम बाबीन/डुबा वाइंडिंग मशीन	25
13	इलेक्ट्रॉनिक जेकार्ड	1



नवीन करघे की तकनीकी मापदण्ड का विवरण


Sl. No	Handlooms/Accessories/ Equipments	Specification with material Details
1	2	3
1	54" REED SPACE WOODEN FRAME LOOM ALONG WITH REED HEALD (suitable for Jacquard mounting)- Complete set for operating Minimum 04 No. treadles	FRAME DETAILS Vertical Poles- 4" x 4" x 6' to 6.5' (Sarai wood) Horizontal Cross Bars- 3" x 2" x 6' to 6.5' (Sarai wood) Side frame bottom cross bars- 3" x 2" x 5' to 6' (Sarai wood) Side frame top cross bars -3" x 2" x 5' to 6' (Sarai wood) Side frame Middle cross bars- 4" x 2" x 6 to 7' (Sarai wood) Back Rest- 3" x 2.5" x 6' to 6.5' (Sarai wood) Treadles- 1.5" to 2" x 1" to 1.25" x 4.5' to 5" (Sarai wood) Short lams- 1" to 1.5" x 1" to 1.25" x 4.5' to 5' (Sarai wood) Lever Stand Suitable for loom size Jack Levers- 1.5" to 2" x 0.75" to 1" x 1.5' to 2' (Sarai wood) Long lams- 1.5" to 2" x 1.5" to 2" x 5' to 5.5" (Sarai wood) OR 2.5" TO 3" dia. Reversing roller arrangement with ball bearing/bush (Sarai wood) Treadle Brackets- 1.5" to 2" x 1.5" to 2" x 5" to 8" (Sarai wood) Weavers seat with middle support - 9" to 10" x 1.5" to 2" x 6' to 7' (Sarai wood) Heald shafts- 1.5" x 0.5" to 0.75" x 5' to 6' (Sarai wood) Treadle Cage for 4 to 6 Treadles (Sarai wood) warp beam- 3" to 4" dia Suitable length for loom size (Sarai wood)



Sl. No	Handlooms/Accessories/ Equipments	Specification with material Details
1	2	3
1	54" REED SPACE WOODEN FRAME LOOM ALONG WITH REED HEALD (suitable for Jacquard mounting)- Complete set for operating Minimum 04 No. treadles	Cloth Beam- 4" dia. Suitable length for loom size (Sarai wood) Cloth Beam Bracket 3.5" to 4" X 3.5" to 4" X 1" Warp Beam Bracket- 3.5 to 4" X 3.5" to 4" X 1" to 1.5" SLEY DETAILS Race Board- 2" to 2.5" x 1.5" to 2" x 56" (Teak Wood) Sley Sword- 3.5" to 4" x 0.75" to 1" x 4" (Teak Wood) Sley holding bar- 2.5" to 3" x 1" to 1.5" x 6.5" to 7" (Teak Wood) Sley middle cross bar -2.5" to 3" x 1" to 1.5" x 54" to 58" (Teak Wood) Reed Cap- 2.5" to 3" x 1.5" to 2" x 54" to 58" (Teak Wood) Shuttle Boxes- 18" to 22" (Shisam wood) Steel Reed - 60 s x 50" Heald - Wire Heald of 27G x 9.5" (2000 Nos.) OR Country Heald (3500Nos.) Iron rod for Take-up motion- 16mm to 20 mm dia. x 2'
2	60" REED SPACE WOODEN FRAME LOOM ALONG WITH REED HEALD (suitable for Jacquard mounting)- Complete set for operating Minimum 04 No. treadles	 FRAME DETAILS Vertical Poles- 4" x 4" x 6' to 6.5' (Sarai wood) Horizontal Cross Bars- 3" x 2" x 6' to 6.5' (Sarai wood) Side frame bottom cross bars- 3" x 2" x 5' to 6' (Sarai wood) Side frame top cross bars -3" x 2" x 5' to 6' (Sarai wood) Side frame Middle cross bars- 4" x 2" x 6 to 7' (Sarai wood) Back Rest- 3" x 2.5" x 6' to 6.5' (Sarai wood) Treadles- 1.5" to 2" x 1" to 1.25 x 4.5' to 5' (Sarai wood) Short lams- 1" to 1.5" x 1" to 1.25" x 4.5' to 5' (Sarai wood)



St. No	Handlooms/Accessories/ Equipments	Specification with material Details
1	2	3
2	60" REED SPACE WOODEN FRAME LOOM ALONG WITH REED HEALD (suitable for Jacquard mounting)- Complete set for operating Minimum 04 No. treadles	Lever Stand Suitable for loom size Jack Levers- 1.5" to 2"x 0.75" to 1" x 1.5' to 2' (Sarai wood) Long lams- 1.5" to 2"x 1.5" to 2"x 5' to 5.5" (Sarai wood) OR 2.5" TO 3" dia. Reversing roller arrangement with ball bearing/bush (Sarai wood) Treadle Brackets-1.5" to 2"x 1.5" to 2"x 5" to 8" (Sarai wood) Weavers seat with middle support - 9" to 10" x 1.5" to 2"x 6' to 7' (Sarai wood) Heald shafts- 1.5" x 0.5" to 0.75" x 5' to 6' (Sarai wood) Treadle Cage for 4 to 6 Treadles (Sarai wood) warp beam-3" to 4" dia Suitable length for loom size Cloth Beam- 4" dia. Suitable length for loom size Cloth Beam Bracket 3.5" to 4" X 3.5" to 4" X 1' Warp Beam Bracket- 3.5 to 4" X 3.5" to 4" X 1' to 1.5' SLEY DETAILS Race Board- 2" to 2.5" x 1.5" to 2" x 60"(Teak Wood) Sley Sword- 3.5" to 4" x 0.75" to 1" x 4' (Teak Wood) Sley holding bar- 2.5" to 3" x 1" to 1.5" x 6.5' to 7' (Teak Wood) Sley middle cross bar -2.5" to 3" x 1" to 1.5" x 60" to 66" (Teak Wood) Reed Cap-2.5" to 3" x 1.5" to 2" x 60" to 66" (Teak Wood) Shuttle Boxes- 18" to 22" (Shisam wood) Steel Reed - 60 s x 50" " Heald Wire Heald of 27G x 9.5" (2000 Nos.) OR Country Heald (3500Nos.) Iron rod for Take-up motion- 16mm to 20 min dia. x 2'



Sl. No	Handlooms/Accessories/ Equipments	Specification with material Details
1	2	3
3	66" REED SPACE WOODEN FRAME LOOM ALONG WITH REED HEALD (suitable for Jacquard mounting)- Complete set for operating Minimum 04 No. treadles	66" REED SPACE WOODEN FRAME LOOM - Sizes of different parts are as above of 60" Wooden Frame Loom proportionately suitable according to 66" reed space wooden frame loom, along with set of Reed and Heald
4	72" REED SPACE WOODEN FRAME LOOM ALONG WITH REED HEALD (suitable for Jacquard mounting)- Complete set for operating Minimum 04 No. treadles	72" REED SPACE WOODEN FRAME LOOM - Sizes of different parts are as above of 60" Wooden Frame Loom proportionately suitable according to 72" reed space wooden frame loom, along with set of Reed and Heald
5	96" REED SPACE WOODEN FRAME LOOM ALONG WITH REED HEALD (suitable for Jacquard mounting)- Complete set for operating Minimum 04 No. treadles	FRAME DETAILS Vertical Poles- 4" x 4.5" x 4" to 4.5" x 6.5" to 7"(Sarai wood) Horizontal Cross Bars- 3" x 3" x 9.5" to 10' to 10.5' (Sarai wood) Side frame bottom cross bars- 3" x 2" x 5' to 5.5' (Sarai wood) Side frame top cross bars -3" x 2" x 5' to 5.5'(Sarai wood) Side frame Middle cross bars- 4" x 2" x 6 to 6.5' (Sarai wood) Back Rest- 3" x 3" x 10' (Sarai wood) Treadles- 2" to 1.5" x 6.5" (Sarai wood) Short lams- 2" x 1" x 6.5' (Sarai wood) Long lams- 2" x 1" x 7' (Sarai wood) Lever Stand with frame set 3" x 2" x 10.5' (Sarai wood) Jack Levers 2" x 1" x 2.5' (Sarai wood) Treadle Brackets- 2" x 2" x 8' (Sarai wood) Weavers seat with middle support - 10" x 1.5" x 10' (Sarai wood) Heald shafts- 1.5" x 0.75" x 9' (Sarai wood) Treadle Cage for 4 to 6 Treadles (Sarai wood) warp beam- 6" dia (Sarai wood)/ 4" dia iron, Cloth Beam- 5" dia (Sarai wood)/ 4" dia iron, Cloth Beam Bracket 4" x 4" x 1' Warp Beam Bracket- 4" x 4" x 1.5' Lam Stand- 2" x 1" x 2'




Sl. No	Handlooms/Accessories/ Equipments	Specification with material Details
1	2	3
5	96" REED SPACE WOODEN FRAME LOOM ALONG WITH REED HEALD (suitable for Jacquard mounting)- Complete set for operating Minimum 04 No. treadles	SLEY DETAILS Race Board- 3.5"x2.5"x96" (Teak Wood) Sley Sword- 4"x1.5"x5' (Teak Wood) Sley holding bar- 3"x1.5"x10.5' to 11' (Teak Wood) Sley middle cross bar -3"x1.5"x96"to 102" (Teak Wood) Reed Cap- 3" x 2.5" x 96" to 102" (Teak Wood) Shuttle Boxes- 22" to 26" (Shisam wood) Steel Reed - 60 s x 96" Heald Wire Heald of 27G x 13.5" (2000 Nos.) Iron rod for Take-up motion- 16mm to 20 min dia. x 2'
6	112" REED SPACE WOODEN FRAME LOOM ALONG WITH REED HEALD (suitable for Jacquard mounting)- Complete set for operating Minimum 04 No. treadles	112" REED SPACE WOODEN FRAME LOOM - Sizes of different parts are as above of 96" Wooden Frame Loom proportionately suitable according to 112" reed space wooden frame loom, along with set of Reed and Heald
7	56" REED SPACE FRAME LOOM WITH HOLLOW IRON FRAME ALONG WITH REED HEALD- (suitable for Jacquard mounting)-Complete set for operating Minimum 04 No. treadles (16 Gage)	FRAME DETAILS Vertical Poles- 3 to 3.5" x 1.5" to 2"x 6' to 6.5' Horizontal Cross Bars- 3"x 1" to 1.5" x 6' to 6.5' Side frame bottom cross bars- 3"x 1" to 1.5"x 5' to 6' Side frame top cross bars -3"x 1" to 1.5" x 5' to 6' Side frame Middle cross bars- 3"x 1" to 1.5"x 6' to 7' Back Rest- 1.5" to 2" . hollow Round Pipe suitable length for loom size. Treadles- 1.5" to 2" x1" to 1.25" x 4.5' to 5' (Sarai Wood) Short lams- 1" to 1.5"x 1" to 1.25" x 4.5' to 5' (Sarai Wood) Lever Stand Suitable for loom size - Jack Levers- 1.5" to 2" x 0.75" to 1" x1.5' to 2' (Sarai Wood) Long lams- 1.5" to 2" 1.5" to 2" x5' to 5.5' (Sarai Wood) OR 2.5" to 3" dia. Reversing roller arrangement with ball bearing/bush (Sarai Wood) Treadle Brackets- 1.5" to 2" x 1.5" to 2 x 5" x 8" (Sarai Wood) Weavers seat- 9" to 10" x 1.5" to 2" x 6' to 7' (Sarai Wood) Heald shafts- 1.5" X 0.5" to 0.75 " X 5' to 6' (Sarai Wood)



Sl. No	Handlooms/Accessories/ Equipments	Specification with material Details
1	2	3
7	56" REED SPACE FRAME LOOM WITH HOLLOW IRON FRAME ALONG WITH REED HEALD- (suitable for Jacquard mounting)-Complete set for operating Minimum 04 No. treadles (16 Gage)	Treadle Cage for 4 to 6 treadles (Sarai Wood) warp beam- 3" to 4" dia. Suitable for loom size Cloth Beam- 4" dia Suitable for loom size Cloth Beam Bracket 3.5" to 4" X 3.5" to 4" X 1' to 1.5' (Sarai Wood) Warp Beam Bracket- 3.5" to 4" X 3.5" to 4" X 1' to 1.5' (Sarai Wood) SLEY DETAILS Race board- 2" to 2.5" x 1.5" to 2" x 56" (Teak wood) Sley swords- 3.5" to 4" x 0.75" to 1" x 4' (Teak wood) Sley holding Bar- 2.5" to 3" x 1" to 1.5" x 6.5' to 7' (Teak wood) Sley Middle cross bar- 2.5" to 3" x 1" to 1.5" x 56" to 60" (Teak wood) Reed Cap- 2.5" to 3" x 1.5" to 2" x 56" to 60" (Teak wood) Shuttle Boxes- 18" to 22" (Shisam wood) Steel Reed - 60 s x 50" OR 76 s x 50" Heald Wire Heald of 27G x 9.5" (2000 Nos.) OR Country Heald (3500Nos.) Iron rod for Take-up motion- 16mm to 20 mm dia. X 2'
8	60" REED SPACE FRAME LOOM WITH HOLLOW IRON FRAME ALONG WITH REED HEALD- (suitable for Jacquard mounting)-Complete set for operating Minimum 04 No. treadles (16 Gage)	FRAME DETAILS Vertical Poles- 3 to 3.5" x 1.5" to 2" x 6' to 6.5' Horizontal Cross Bars- 3" x 1" to 1.5" x 6' to 6.5' Side frame bottom cross bars- 3" x 1" to 1.5" x 5' to 6' Side frame top cross bars- 3" x 1" to 1.5" x 5' to 6' Side frame Middle cross bars- 3" x 1" to 1.5" x 6' to 7' Back Rest- 1.5" to 2". hollow Round Pipe suitable length for loom size. Treadles- 1.5" to 2" x 1" to 1.25" x 4.5' to 5' (Sarai Wood) Short lams- 1" to 1.5" x 1" to 1.25" x 4.5' to 5' (Sarai Wood) Lever Stand Suitable for loom size - Jack Levers- 1.5" to 2" x 0.75" to 1" x 1.5' to 2' (Sarai Wood) Long lams- 1.5" to 2" 1.5" to 2" x 5' to 5.5' (Sarai Wood) OR 2.5" to 3" dia. Reversing roller arrangement with ball bearing/bush (Sarai Wood)



Sl. No	Handlooms/Accessories/ Equipments	Specification with material Details
1	2	3
8	60" REED SPACE FRAME LOOM WITH HOLLOW IRON FRAME ALONG WITH REED HEALD- (suitable for Jacquard mounting)-Complete set for operating Minimum 04 No. treadles (16 Gage)	Treadle Brackets- 1.5" to 2" x 1.5" to 2 x 5" x 8" (Sarai Wood) Weavers seat- 9" to 10" x 1.5" to 2" x 6' to 7' (Sarai Wood) Heald shafts- 1.5" X 0.5" to 0.75 " X 5.5' to 6" (Sarai Wood) Treadle Cage for 4 to 6 treadles (Sarai Wood) warp beam- 3" to 4" dia. Suitable for loom size Cloth Beam- 4" dia Suitable for loom size Cloth Beam Bracket 3.5" to 4" X 3.5" to 4" X 1' (Sarai Wood) Warp Beam Bracket- 3.5" to 4" X 3.5" to 4" X 1' to 1.5' (Sarai Wood)
		SLEY DETAILS
		Race board- 2" to 2.5" x 1.5" to 2" x 60" (Teak wood)
		Sley swords- 3.5" to 4" x 0.75" to 1" x 4' (Teak wood)
		Sley holding Bar- 2.5" to 3" x 1" to 1.5" x 6.5' to 7' (Teak wood)
		Sley Middle cross bar- 2.5" to 3" x 1" to 1.5" x 60" to 66" (Teak wood)
		Reed Cap- 2.5" to 3" x 1.5" to 2" x 60" to 66 " (Teak wood)
		Shuttle Boxes- 18" to 22" (Shisam wood)
		Steel Reed - 60 s x 50" OR 76 s x 50"
		Heald Wire Heald of 27G x 9.5" (2000 Nos.) OR Country Heald (3500Nos.)
		Iron rod for Take-up motion- 16mm to 20 mm dia. X 2'
9	66" REED SPACE FRAME LOOM WITH HOLLOW IRON FRAME ALONG WITH REED HEALD- Sizes of different parts are as above suitable according to 60" reed space frame loom.	66" REED SPACE FRAME LOOM WITH HOLLOW IRON FRAME - Sizes of different parts are as above of 60" Iron Frame Loom proportionately suitable according to 66" reed space iron frame loom, along with set of Reed and Heald as above
10	72" REED SPACE FRAME LOOM WITH HOLLOW IRON FRAME ALONG WITH REED HEALD- Sizes of different parts are as above suitable according to 60" reed space frame loom.	72" REED SPACE FRAME LOOM WITH HOLLOW IRON FRAME - Sizes of different parts are as above of 60" Iron Frame Loom proportionately suitable according to 72" reed space iron frame loom, along with set of Reed and Heald as above (for cotton weaving)



Sl. No	Handlooms/Accessories/ Equipments	Specification with material Details
1	2	3
11	96" REED SPACE FRAME LOOM WITH HOLLOW IRON FRAME ALONG WITH REED HEALD- (suitable for Jacquard mounting)-Complete set for operating Minimum 04 No. treadles (14 Gage)	FRAME DETAILS Vertical Poles- 3" to 3.5" x 1.5" to 2"x 6.5" to 7" Horizontal Cross Bars- 3"x 1" to 1.5" x 10" Side frame bottom cross bars- 3"x 1" to 1.5"x 5' to 5.5' Side frame top cross bars -3"x 1" to 1.5"x 5' to 5.5' Side frame Middle cross bars- 3"x 1" to 1.5"x 6' to 6.5' Back Rest- 3"X 1" to 1.5"x 10' OR 3.0" to 3.5" . hollow Round Pipe suitable length for loom size. Treadles- 2" x1.5"x5.5' (Sarai Wood) Short lams- 2"X1"X6.5" (Sarai Wood) Long lams-2"X1"X7" (Sarai Wood) Lever Stand with frame set - 3" x 1" to 1.5" x 10.5" (Sarai Wood) Jack Levers 2" x 1" x 2.5' (Sarai Wood) Treadle Brackets-2"x 2"x 8" (Sarai Wood) Weavers seat-10" x 1.5"x 10' to 10.5' (Sarai Wood) Heald shafts- 1.5" X 0.75 " X 9' (Sarai Wood) Treadle Cage for 4 to 6 treadles (Sarai Wood) warp beam- 4.5" to 5" dia. Suitable for loom size Cloth Beam- 4.5" to 5" dia Suitable for loom size Cloth Beam Bracket 4" X 4" X 1' Warp Beam Bracket- 4" X 4" X 1.5' Lam stand- 2" X 1" X 2' SLEY DETAILS Race board- 3.5"x2.5"x 96" (Teak wood) Sley swords- 4" x 1.5"x 5' (Teak wood) Sley holding Bar- 3"x 1.5" x 10.5' to 11' (Teak wood) Sley Middle cross bar- 3" x1.5" x 96" to 102" (Teak wood) Reed Cap- 3"x 2.5"x 96" to 102" (Teak wood)



Sl. No	Handlooms/Accessories/ Equipments	Specification with material Details
1	2	3
11	96" REED SPACE FRAME LOOM WITH HOLLOW IRON FRAME ALONG WITH REED HEALD- (suitable for Jacquard mounting)-Complete set for operating Minimum 04 No. treadles (14 Gage)	Shuttle box 22" to 26" (Shisam wood) Steel Reed 60 s x 96" Heald- wire Heald of 27 G X 13.5" (2000 Nos.) Iron rod for Take-up motion- 16mm to 20 mm dia. X 2'
12	112" REED SPACE FRAME LOOM WITH HOLLOW IRON FRAME ALONG WITH REED HEALD- Sizes of different parts are as above suitable according to 96" reed space frame loom.	112" REED SPACE FRAME LOOM WITH HOLLOW IRON FRAME - Sizes of different parts are as above of 96" Iron Frame Loom proportionately suitable according to 112" reed space iron frame loom, along with set of Reed and Heald as above (for cotton weaving)
13	PIT LOOM ALONG WITH REED HEALD (suitable for Dobby mounting Complete set.)	56" REED SPACE WOODEN PIT LOOM:- Sizes of different parts are as above 56" reed space Wooden frame loom suitable for 56" reed space pit loom, including installation and pitting charges along with set of Reed and Heald (for Silk/Cotton weaving). 60" REED SPACE WOODEN PIT LOOM:- Sizes of different parts are as above 60" reed space Wooden frame loom suitable for 60" reed space pit loom, including installation and pitting charges along with set of Reed and Heald (for Silk/Cotton weaving).



Joint Director Handloom
Raipur

(A. Ayaz)

सहायक उपकरणों की तकनीकी मापदण्ड का विवरण

Sl. No	Handlooms/Accessories/ Equipments	Specification with material Details
1	2	3
1	Take-up & let off motions on the existing handloom (incl. fitting charges)	5-wheel take – up motion with complete set including Spike roller pipe, Spikes roller and Let-off motion set including fitting charges (on the existing loom)
2	Pneumatic jacquard System	Pneumatic jacquard lifting system for set of 2 handlooms. Pneumatic jacquard lifting system for set of 4 handlooms.
3	Motorized lifting device for jacquard (single lever)	Motorized lifting device should be installed with existing mechanical jacquard of 120 hooks, 240hooks & pairs of both capacities in existing Pit loom/Frame loom. 1-φ 230 V ac motor of ¼ H.P. with producing high torque. Main card 2.5 sq. mm for connecting Motorized lifting device to weavers peddle. Free installation with required items like cable, switches, bolt & nut etc. & demo at beneficiaries end.
4	Multi box motion device	2 X 1 Multiple Box motion device (Double Peti)
5	Multiple Buti Weaving Sley	Multiple buti (Spot motif) weaving sley having capacity of minimum 9 buti (spot) in 50" working spot and 60" reed space.
6	Twin Cloth Weaving mechanism	Twin cloth weaving mechanism upto 66" including fitting Charges Twin cloth weaving mechanism upto 72" including fitting Charges
7	Jacquard with complete set (punching plate box and puncher, Comber board frame-6½X 1½ Sal wood, Comber board perforated net, Jacquard fitting frame-3" X 2", neck cord, yellow cord for harness, Top and Bottom coupling (Nylon), Lingos 10" to 12", including installation	100 hooks 200 hooks 240 hooks 300 hooks



Sl. No	Handlooms/Accessories/ Equipments	Specification with material Details
1	2	3
8	Dobby	8 lever Dobby with full accessories (lattice chain of 25 lags and 200 pegs) 16 lever Dobby with full accessories (lattice chain of 25 lags and 200 pegs) 24 lever Dobby with full accessories (lattice chain of 50 lags and 200 pegs) 32 lever Dobby with full accessories (lattice chain of 25 lags and 200 pegs)
9	Reed (Steel)	36 to 50 No. ($3\frac{1}{4}$ X $4\frac{1}{2}$) per Inch 52 to 80 No. ($3\frac{1}{4}$ X $4\frac{1}{2}$) Per 100 Dent 84 to 100 No. ($3\frac{1}{4}$ X $4\frac{1}{2}$) Per 100 Dent 36 to 48 Per 100 Eyes 52 to 80 Per 100 Eyes
10	Heald (Nylon)	27 G 13" size wire healds (Pkt. of 1000 Pcs.) 27 G $9\frac{1}{2}$ " size wire healds (Pkt. of 1000 Pcs.)
11	Heald (Wire)	Size 12"
12	Simple Wooden Shuttle (Weight not more than 230 gm.)	Size 12"
13	Half Compress Shuttle	Size 12"
14	Full Compress Shuttle	Size 12"
15	Nylon bobbin	Nylon bobbin of 2.5" X 5" size
16	Nylon Pirn	Nylon pirn of 4" size Nylon pirn of 5" size Nylon pirn of 6" size



Sl. No	Handlooms/Accessories/ Equipments	Specification with material Details
1	2	3
17	WARP BEAM (Iron)	5" dia For 54" loom 5" dia for 60" loom 5" dia for 66" loom 5" dia for 72" loom 6" dia for 96" loom 6" dia for 112" loom
18	CLOTH BEAM (Iron)	4" dia For 54" loom 4" dia for 60" loom 4" dia for 66" loom 4" dia for 72" loom 5" dia for 96" loom 5" dia for 112" loom
19	Normal Warping Machine	Warping Drum- Warping Drum of 5 meter Circumference and 110" width having minimum 03 rings, each ring having 12 iron spokes of 1" x 1" square shaped. The bars over ring should be 2.5" to 3" x 2 to 2.5" wooden bar (Sal wood) or 1.5" x 2" iron bar. The axle of 2.5" to 3" dia iron pipe with ball bearing on both sides for revolution. Belt and dead weight type tension device and suitable measuring arrangement. The warping drum should be capable for warping length 300-350 m. Drum stand-3.5' to 4' height made of 3" x 3" iron C channel with robust construction, adequate for 300-350 meter warping. Beaming Stand iron beaming stand adjustable for various sizes of warp beam and capable for beaming 300-350 meter of warp. Creel Stand 150 bobbins capacity creel, heck, leasing device, for winding iron rod etc. A complete set.



Sl. No	Handlooms/Accessories/ Equipments	Specification with material Details
1	2	3
20	Motorized Warping Machine	Sizes are as above with complete set of 0.5 HP capacity motor with suitable gearing arrangement for warping and beaming with suitable drive for jerk free/smooth winding/converting of theards into warp sheet and transfer of warp sheet to weavers beam.
21	Motorized Pirm/cum bobbin/dubba Winding machine	Cycle wheel charaka (Chain & Sprocket system) with mill spindle. High speed motorized pirm/bobbin winding machine with 0.25-0.5 H.P. capacity electric motor & regulator for speed control. High Speed motorized pirm cum bobbin/dubba winding machine (Capacity- Minimum 06 Spindle) 640 Hook Electronic Handloom Jacquard with Position Control Motor for Self-Driving Mechanism.
22	Electronic Handloom Jacquard Capacity 640 Hook.	Power Consumption including Motor = 500 Watt. Control Panel wit USB Pen drive Support Jacquard Run-Trigger Paddle Switch Jacquard Guide Board Jacquard Harness Connector / Linker



(A. Yaz)

Joint Director Handloom
Raipur



-:: नवीन करघे क्रय हेतु दर पत्रक ::-


क्र.	नवीन करघे का नाम	समस्त कर सहित दर (जी.एस.टी. एवं एफ. ओ.आर. फीटिंग सहित)
1	2	3
1	54" REED SPACE WOODEN FRAME LOOM ALONG WITH REED HEALD (suitable for Jacquard mounting)- Complete set for operating Minimum 04 No. treadles	
2	60" REED SPACE WOODEN FRAME LOOM ALONG WITH REED HEALD (suitable for Jacquard mounting)- Complete set for operating Minimum 04 No. treadles	
3	66" REED SPACE WOODEN FRAME LOOM ALONG WITH REED HEALD (suitable for Jacquard mounting)- Complete set for operating Minimum 04 No. treadles	
4	72" REED SPACE WOODEN FRAME LOOM ALONG WITH REED HEALD (suitable for Jacquard mounting)- Complete set for operating Minimum 04 No. treadles	
5	96" REED SPACE WOODEN FRAME LOOM ALONG WITH REED HEALD (suitable for Jacquard mounting)- Complete set for operating Minimum 04 No. treadles	
6	112" REED SPACE WOODEN FRAME LOOM ALONG WITH REED HEALD (suitable for Jacquard mounting)- Complete set for operating Minimum 04 No. treadles	
7	56" REED SPACE FRAME LOOM WITH HOLLOW IRON FRAME ALONG WITH REED HEALD- (suitable for Jacquard mounting)-Complete set for operating Minimum 04 No. treadles (16 Gage)	



क्रमश:-2

क्र.	नवीन करघे का नाम	समस्त कर सहित दर (जी.एस.टी. एवं एफ. ओ.आर. फीटिंग सहित)
1	2	3
8	60" REED SPACE FRAME LOOM WITH HOLLOW IRON FRAME ALONG WITH REED HEALD- (suitable for Jacquard mounting)-Complete set for operating Minimum 04 No. treadles (16 Gage)	
9	66" REED SPACE FRAME LOOM WITH HOLLOW IRON FRAME ALONG WITH REED HEALD- Sizes of different parts are as above suitable according to 60" reed space frame loom.	
10	72" REED SPACE FRAME LOOM WITH HOLLOW IRON FRAME ALONG WITH REED HEALD- Sizes of different parts are as above suitable according to 60" reed space frame loom.	
11	96" REED SPACE FRAME LOOM WITH HOLLOW IRON FRAME ALONG WITH REED HEALD- (suitable for Jacquard mounting)-Complete set for operating Minimum 04 No. treadles (14 Gage)	
12	112" REED SPACE FRAME LOOM WITH HOLLOW IRON FRAME ALONG WITH REED HEALD- Sizes of different parts are as above suitable according to 96" reed space frame loom.	
13	56" REED SPACE WOODEN PIT LOOM:- Sizes of different parts are as above 56" reed space Wooden frame loom suitable for 56" reed space pit loom, including installation and pitting charges along with set of Reed and Heald (for Silk/Cotton weaving).	
14	60" REED SPACE WOODEN PIT LOOM:- Sizes of different parts are as above 60" reed space Wooden frame loom suitable for 60" reed space pit loom, including installation and pitting charges along with set of Reed and Heald (for Silk/Cotton weaving).	

नोट:- नवीन करघे हेतु तकनीकी मापदण्ड "परिशिष्ट-एक संलग्न है, जिसमें उल्लेखित मापदण्डों के अनुसार ही क्रमांक 1 से 14 तक के उपकरणों के लिए दर अंकित करें।



प्रोपाईटर के हस्ताक्षर
एवं सील

-:: अन्य सहायक उपकरण क्रय हेतु दर पत्रक ::-

क्र.	अन्य सहायक उपकरणों का नाम	समस्त कर सहित दर (जी.एस.टी. एवं एफ.ओ.आर. फीटिंग सहित)
1	2	3
1	Take-up & let off motions on the existing handloom (incl. fitting charges)	
2	Pneumatic jacquard System	Pneumatic jacquard lifting system for set of 2 handlooms.
		Pneumatic jacquard lifting system for set of 4 handlooms.
3	Motorized lifting device for jacquard (single lever)	
4	Multi box motion device	
5	Multiple Buti Weaving Sley	
6	Twin Cloth Weaving machanism	Twin cloth weaving mechanism upto 66" including fitting Charges.
		Twin cloth weaving mechanism upto 72" including fitting Charges.
7	Jacquard with complete set (punching plate box and puncher, Comber board frame- 6½X 1½ Sal wood, Comber board perforated net, Jacquard fitting frame- 3" X 2, neck cord, yellow cord for harness, Top and Bottom coupling (Nylon), Lingos 10"/12",) including installation	100 hooks
		200 hooks
		240 hooks
		300 hooks
8	Dobby	8 lever Dobby with full accessories (lattice chain of 25 lags and 200 pegs)
		16 lever Dobby with full accessories (lattice chain of 25 lags and 200 pegs)
		24 lever Dobby with full accessories (lattice chain of 50 lags and 200 pegs)
		32 lever Dobby with full accessories (lattice chain of 25 lags and 200 pegs)

क्रमश:-2



क्र.	अन्य सहायक उपकरणों का नाम		समस्त कर सहित दर (जी.एस.टी. एवं एफ.ओ.आर. फीटिंग सहित)
1	2		3
9	Reed (Steel)	36 to 50 No. ($3\frac{1}{4}$ X $4\frac{1}{2}$) per Inch	
		52 to 80 No. ($3\frac{1}{4}$ X $4\frac{1}{2}$) per 100 Dent	
		84 to 100 No. ($3\frac{1}{4}$ X $4\frac{1}{2}$) per 100 Dent	
10	Heald (Nylon)	36 to 48 Per 100 Eyes	
		52 to 80 Per 100 Eyes	
11	Heald (Wire)	27 G 13" size wire healds (Pkt. of 1000 Pcs.)	
		27 G 9½" size wire healds (Pkt. of 1000 Pcs.)	
12	Simple Wooden Shuttle (Weight not more than 230 gm.)	Size 12"	
13	Half Compress Shuttle	Size 12"	
14	Full Compress Shuttle	Size 12"	
15	Nylon bobbin	Nylon bobbin of 2.5" X 5" size	
16	Nylon Pirn	Nylon pirn of 4" size	
		Nylon pirn of 5" size	
		Nylon pirn of 6" size	
17	WARP BEAM (Iron)	5" dia For 54" loom	
		5" dia for 60" loom	
		5" dia for 66" loom	
		5" dia for 72" loom	
		6" dia for 96" loom	
		6" dia for 112" loom	



क्रमश:-3

क्र.	अन्य सहायक उपकरणों का नाम		समस्त कर सहित दर (जी.एस.टी. एवं एफ.ओ.आर. फीटिंग सहित)
1	2		3
18	CLOTH BEAM (Iron)	4" dia For 54" loom	
		4" dia for 60" loom	
		4" dia for 66" loom	
		4" dia for 72" loom	
		5" dia for 96" loom	
		5" dia for 112" loom	
19	Normal Warping Machine		
20	Motorized Warping Machine		
21	Motorized Pirn/cum bobbin/dubba Winding machine		
22	Electronic Handloom Jacquard Capacity 640 Hook.		

नोट:- अन्य सहायक उपकरणों हेतु तकनीकी मापण्ड “ परिशिष्ट-दो” संलग्न है, जिसमें उल्लेखित मापदण्डों के अनुसार ही क्रमांक 1 से 22 तक के उपकरणों के लिए दर अंकित करें।

प्रोपाईटर के हस्ताक्षर
एवं सील

